

BEARING,BALL, SKF # 7306 BG

SI	Items Description	Unit	Qty
1	<p>BEARING,BALL,RADIAL, SKF# 6208ZZC3</p> <p>BEARING BALL, RADIAL, SINGLE ROW, CONRAD TYPE,</p> <p>LIGHT (200) SERIES, WITH TWO SHIELDS,</p> <p>AND RADIAL CLEARANCE GREATER THAN NORMAL.</p> <p>DIMENSIONS: ID 40 X OD 80 X WIDTH 18MM</p>	Ea	20
2	<p>BEARING, BALL: MRC # 5312MFF</p> <p>DESCRIPTION: BEARING, BALL</p> <p>BEARING NO: 5312 MFF (MRC OR EQUAL)</p> <p>MATERIAL: STEEL</p> <p>ADDITIONAL INFORMATION: WEIGHT: 4 LBS (1.5 KG)</p>	Ea	1
3	<p>BEARING,BALL,RADIAL,SINGL ROW,SKF # 6217C3</p> <p>BEARING, BALL, RADIAL, SINGLE ROW, RIGID JOURNAL,</p> <p>CONRAD TYPE, LIGHT SERIES, W/RADIAL</p> <p>CLEARANCE GREATER THAN NORMAL, METRIC SIZES.</p> <p>DIMENSIONS: ID 85 X OD 150 X WIDTH 28MM</p>	Ea	2
4	<p>BEARING,BALL : SKF # 6222-ZZ</p> <p>BEARING, BALL, RADIAL, SINGLE ROW, RIGID JOURNAL,CONRAD TYPE, LIGHT SERIES, W/TWO SHIELDS,METRIC SIZES</p> <p>(METALLIC CAGE/ RETAINER'S ONLY.)</p> <p>DIMENSIONS: ID 110 X OD 200 X WIDTH 38MM</p>	Ea	4
5	<p>BEARING, BALL: SKF # 7307BECBM</p> <p>BEARING, BALL, SINGLE ROW, ANGULAR CONTACT, MEDIUM SERIES, METRIC SIZES</p> <p>(METALLIC CAGE/RETAINER'S ONLY).</p>	Ea	4

	(CUSTOM CODE 746000)		
	DIMENSIONS: ID 35 X OD 80 X WIDTH 21MM		
6	BEARING, BALL: SKF # 3205 BEARING, BALL, DOUBLE ROW, ANGULAR CONTACT, LIGHT SERIES, METRIC SIZES. (METALLIC CAGE/RETAINER'S ONLY). DIMENSIONS: ID 25 X OD 52 X WIDTH 20.2MM	Ea	4
7	BEARING, BALL, SKF # 7306 BG BEARING, BALL, SINGLE ROW, DUPLEX ANGULAR CONTACT, MATCHED PAIR, MEDIUM SERIES, WITH STEEL CAGE, METRIC SIZES. (NON-METALLIC CAGE NOT ACCEPTABLE) DIMENSIONS: ID 30 X OD 72 X WIDTH 38MM	Pair	8
8	BEARING, BALL SKF # 3207 BEARING, BALL, ANGULAR CONTACT, DOUBLE ROW, LIGHT SERIES, WITH STEEL CAGE, METRIC SIZES. (NON-METALLIC CAGE NOT ACCEPTABLE) DIMENSIONS: ID 35 X OD 72 X WIDTH 26.99MM	Ea	3
9	BEARING, BALL SKF # 3210 BEARING, BALL, ANGULAR CONTACT, DOUBLE ROW, LIGHT SERIES, WITH STEEL CAGE, METRIC SIZES. (NON-METALLIC CAGE NOT ACCEPTABLE) DIMENSIONS: ID 50 X OD 90 X WIDTH 30.16MM	Ea	3

SI	Items Description	Unit	Qty
	Approved Manufacturer: SKF, NSK & FAG Only		
1	BEARING, ROLL SKF # 30204	Ea	2

	<p>BEARING, ROLLER, TAPERED, INTERNATIONAL STANDARD,</p> <p>LIGHT SERIES, WITH STEEL CAGE, METRIC SIZES</p> <p>DIMENSIONS: ID 20 X OD 47 X WIDTH 14MM</p>		
2	<p>BEARING,BALL SKF # 3206</p> <p>BEARING, BALL, ANGULAR CONTACT, DOUBLE ROW, LIGHT</p> <p>SERIES, WITH STEEL CAGE, METRIC SIZES.</p> <p>(NON-METALLIC CAGE NOT ACCEPTABLE)</p> <p>DIMENSIONS: ID 30 X OD 62 X WIDTH 23.81MM</p>	Ea	2
3	<p>BEARING,BALL SKF # 3212</p> <p>BEARING, BALL, ANGULAR CONTACT, DOUBLE ROW, LIGHT</p> <p>SERIES, WITH STEEL CAGE, METRIC SIZES.</p> <p>(NON-METALLIC CAGE NOT ACCEPTABLE)</p> <p>DIMENSIONS: ID 60 X OD 110 X WIDTH 36.51MM</p>	Ea	2
4	<p>BEARING,BALL SKF# 3308-NR</p> <p>BEARING, BALL, ANGULAR CONTACT, DOUBLE ROW, DEEP GROOVE</p> <p>SOLID RACE, WITH SNAP RING, MEDIUM SERIES,</p> <p>STEEL CAGE, METRIC SIZES.</p> <p>(NON-METALLIC CAGE NOT ACCEPTABLE)</p> <p>DIMENSIONS: ID 40 X OD 90 X WIDTH 36.51MM</p>	Ea	5
5	<p>BEARING,BALL SKF # 6308-C3</p> <p>BEARING, BALL, RADIAL, SINGLE ROW, RIGID JOURNAL,</p> <p>CONRAD TYPE, MEDIUM SERIES, W/RADIAL,</p> <p>CLEARANCE GREATER THAN NORMAL, METRIC SIZES, WITH STEEL CAGE.</p> <p>(NON-METALLIC CAGE NOT ACCEPTABLE)</p>	Ea	4

	DIMENSIONS: ID 40 X OD 90 X WIDTH 23MM		
6	BEARING,BALL SKF # 7305 BG BEARING, BALL, SINGLE ROW, DUPLEX ANGULAR CONTACT, MATCHED PAIR, MEDIUM SERIES, WITH STEEL CAGE, METRIC SIZES. (NON-METALLIC CAGE NOT ACCEPTABLE) DIMENSIONS: ID 25 X OD 62 X WIDTH 34MM	Pair	2
7	BEARING,BALL SKF # 6310-C3 BEARING, BALL, RADIAL, SINGLE ROW, RIGID JOURNAL, CONRAD TYPE, MEDIUM SERIES, W/RADIAL, CLEARANCE GREATER THAN NORMAL, METRIC SIZES, WITH STEEL CAGE. (NON-METALLIC CAGE NOT ACCEPTABLE) DIMENSIONS: ID 50 X OD 110 X WIDTH 27MM	Ea	7
8	BRNG,BALL, RADL, SINGL ROW, SKF # 6203 BEARING, BALL, RADIAL, SINGLE ROW, CONRAD TYPE, LIGHT (200) SERIES METRIC SIZES NOTES TO VENDOR: PROVIDE EQUIVALENT CATALOGUE SHEET, INDICATING ENQUIRED BEARING NUMBER AND OFFERED BEARING NUMBER, TO JUSTIFY EQUIVALENCE, IF ALTERNATIVE MANUF.OFFERED WITHOUT WHICH OFFER SHALL BE REJECTED. DIMENSIONS: ID 17 X OD 40 X WIDTH 12MM	Ea	2