

# SKF CMXA 80-M-K-SL

EQUIPMENT FOR MEASUREMENT AND VIBRATION ANALYSIS MICROLOG AX M-SERIES  
4-CHANNEL SKF CMXA 80-M-K-SL

EQUIPMENT COMPOSED BY:

- CMXA 80-K
- SL UNIT OF FOUR CHANNELS.
- CD-ROM USER'S MANUAL AND LITERATURE.
- CMAC 5070 LONG-DURATION BATTERY PACK, 8 HOURS OF CONTINUOUS WORK.
- CMAC 5022 POWER ADAPTER BATTERY CHARGER.
- CMAC 5019 USB CABLE FOR COMMUNICATION.
- CMSS 2200 TWO (2) INDUSTRIAL ACCELEROMETERS.
- CMSS 908-MD TWO (2) MAGNETIC BASES FOR ACEROMETERS.
- CMAC 5209 TWO (2) SENSOR CABLES, COILED.
- CMAC 5074 TWO (2) SCREEN PROTECTORS.
- CMAC 5069 TRANSPORT BAG.
- CMAC 5068 DOCKING STATION.
- CMAC 5077 SD MEMORY 1 GB.
- CMAC 5201 SERIAL COMMUNICATION CABLE, 9 PIN, RS-232. MAIN FEATURES.
- RANGE OF MEASUREMENT OF UP TO 80 KHZ., (4,800,000 CPM).
- 6.4 "VGA SCREEN (640X480 PIXELS).
- 25,600 LINES IN DATA COLLECTION THROUGH 1 CHANNEL.
- SIMULTANEOUS TRIAXIAL MEASUREMENT.
- 4 CHANNELS OUT OF ROUTE.
- INDEPENDENT TRIGGER ENTRY.
- ALLOWS VISUALIZATION IN DARK SPACES.

SPECIFY GUARANTEES.

2) STROBOSCOPE SKF TMRS 1, COMPACT PVC, LCD DISPLAY INCLUDES BATTERY,  
ADAPTER, REPLACEMENT LAMP AND BAG USE: MOLLING SAG