BEARING:NDE, PART # 7312 BT1 DBC3

	BEARING,BALL, PART # 7305 BG BEARING, BALL, SINGLE ROW, DUPLEX ANGULAR CONTACT, MATCHED PAIR, MEDIUM SERIES, WITH STEEL CAGE, METRIC SIZES. (NON-METALLIC CAGE NOT ACCEPTABLE) **DIMENSIONS: ID 25 X OD 62 X WIDTH 34MM**	Pair	4
8	**BEARING, BALL, PART # 6210-C3** BEARING, BALL, RADIAL, SINGLE ROW, RIGID JOURNAL, CONRAD TYPE, LIGHT SERIES, WITH RADIAL CLEARANCE GREATER THAN NORMAL, METRIC SIZES, WITH STEEL CAGE. (NON-METALLIC CAGE NOT ACCEPTABLE) **DIMENSIONS: ID 50 X OD 90 X WIDTH 20MM**	Ea	1
9	**BEARING, BALL, PART # 6212** BEARING, BALL, RADIAL, SINGLE ROW, RIGID JOURNAL, CONRAD TYPE, LIGHT SERIES, METRIC SIZES, WITH STEEL CAGE. (NON-METALLIC CAGE NOT ACCEPTABLE) **DIMENSIONS: ID 60 X OD 110 X WIDTH 22MM**	Ea	1
10	**BEARING, PART # NU309** BEARING, ROLLER, CYLINDRICAL, RIGID RADIAL, SINGLE ROW, SELF-CONTAINED OUTER RACE AND STRAIGHT INNER RACE, WITH STEEL CAGE, MEDIUM SERIES. METRIC SIZES. (NON-METALLIC CAGE NOT ACCEPTABLE) **DIMENSIONS: ID 45 X OD 100 X WIDTH 25MM**	Ea	1
11	**BEARING:NDE, PART # 7312 BT1 DBC3**	Ea	1

	SPARES FOR FUJI MOTOR INDUCTION MOTOR, TYPE: MLA1310D, FRAME: 315 S, 100 HP, 440 VOLT, 117 AMP, 50 HZ, 3 PHASE, 2 POLES, 2965 RPM, RATING: M.C.R., INSULATION CLASS F, COOLANT 50 DEG. C, RULE: 1EC34-1-1969, TYPICAL SR.NO. 84118258DS-1, NON-SPARKING MOTOR SUITABLE FOR CL 1-DIV.2 GR.D. (FOR EBARA STRIPPED SOUR WATER PUMPS, MODEL: 100 LPWM (40H), SR.NO. RE10256-04, BEARING, NON DRIVE END SIDE, **DIMENSIONS: N/A**		
12	**BEARING,BALL:DEEP GROOVE,** **ROW 1,20 MM ID,47 MM OD,14 MM WD,OPEN, PART # 6204** BEARING, BALL, RADIAL, SINGLE ROW, RIGID JOURNAL, CONRAD TYPE, LIGHT SERIES, METRIC SIZES. (METALLIC CAGE/ RETAINER'S ONLY) **DIMENSIONS: ID 120 X OD 20 X WIDTH 14MM**	Ea	1
13	**BEARING,BALL PART # 3206** BEARING, BALL, ANGULAR CONTACT, DOUBLE ROW, LIGHT SERIES, WITH STEEL CAGE, METRIC SIZES. (NON-METALLIC CAGE NOT ACCEPTABLE) **DIMENSIONS: ID 30 X OD 62 X WIDTH 23.81MM**		