

PLUMMER BLOCK;SNL532;SKF23132CCK/W33

Material Description	Long Text	Manufacturer Pa
BEARING UNIT ; FYJ 100 TF	BEARING:FLANGED BEARING UNIT;TYPE:SQ.FLANGED;MODEL:FYJ 100 TF;BORE DIAMETER:100MM;FINISHED LENGTH:107MM;OVERALL WIDTH:265MM SQUARE; MAKE:SKF; ADDITIONAL DATA:UNIT IS BEARING WITH HOUSING;FOUR HOLES MOUNTING	FYJ 100 TF
BEARING UNIT ; SYJ 80 TF	BEARING UNIT:Y-BEARING PLUMMER BLOCK UNIT;MODEL:SYJ 80 TF;BORE DIAMETER:80MM;BASE LENGTH:292MM;HOUSING HEIGHT:176MM;HOUSING WIDTH:78 MM;MATERIAL:HOUSING CI;ROTATING ELEMENT LOCKING METHOD:SCRUB SREW;MAKE:SKF;ADDITIONAL DATA:UNIT IS BEARING WITH HOUSING	SYJ 80 TF
PLUMMER BLOCK;SNL530;SKF	HOUSING:PLUMMER BLOCK; AXLE DIAMETER: 135 MM;FORM CONSTRUCTION:SNL 530;SEALING: LABYRINTH SEAL;BORE SHAPE: ROUND;USAGE LOCATION: USE D FOR CONVEYOR SYSTEMS;ADDITIONAL DATA: MAKE:SKF; MATERIAL TO BE SUPPLIED WITH LABRYINTH SEAL.	SNL 530
PLUMMER BLOCK;SNL532;SKF	HOUSING:PLUMMER BLOCK; AXLE DIAMETER: 140 MM;FORM CONSTRUCTION:SNL 530;SEALING: LABYRINTH SEAL;BORE SHAPE: ROUND;USAGE LOCATION: USE D FOR CONVEYOR SYSTEMS;ADDITIONAL DATA: MAKE:SKF; MATERIAL TO BE SUPPLIED WITH LABRYINTH SEAL	SNL532
6208 2RS1 C3 BEARING;SKF	6208 2RS1 C3 BEARING;PART NO:6208-2RS1/C3;MANUFACTURER:SKF	6208-2RS1/C3
BALL BEARING;40X90X23MM, 6308-2Z/C3	STANDARD BALL BEARING;40X90X23MM;CLEARANCE CLASS:C3, 6308-2Z/C3	6308 ZZ C3
BALL BEARING;220X340X56MM, 6044 M/C3	STANDARD BALL BEARING;220X340X56MM;CLEARANCE CLASS:C3, 6044 M/C3	6044 M C3
SEAL:OIL SEAL; SM 4.125X5.250X0.500	SEAL:OIL SEAL; SM 4.125X5.250X0.500;INSIDE DIAMETER: 4.125 INCH;OUTSIDE DIAMETER: 5.250 INCH;THICKNESS: 0.500 INCH;STYLE DESIGNATOR: SBE / SBF;COLOR: BLACK;CONSTRUCTION:METAL CLADE SEAL;MATERIAL:NBR WITH STEEL RING;TEMPERATURE RATING:100DEG C	0
BEARING,SINGLE ROW CYL ROLLER,NJ410C5	BEARING:ROLLER;CYLINDRICAL; BORE SHAPE: CYLINDRICAL ;STYLE DESIGNATOR:NJ	NJ410C5

	410 C5;INSIDE DIAMETER:50 MM ;OUTSIDE DIAMETER:130 MM ;BODY MOUNTING HOLE ACCOMMODATION WIDTH:31 MM;ROW QUANTITY:1;CAGE MATERIAL:STANDARD;CLEARANCE: C5;MAKE:SKF	
SEAL;OIL;50X65X8 MM; SINGLT LIP BEARING;BALL;DEEP GROOVE;6207 C3	SEAL;OIL;50X65X8 MM; SINGLT LIP BEARING:BALL;DEEP GROOVE; STYLE DESIGNATOR: 6207 C3;BORE SHAPE: CYLINDRICAL ;BORE DIAMETER: 35 MM;OVERALL OUTSIDE DIAMETER: 72 M M;OVERALL WIDTH: 17 MM;ROW QUANTITY: 1;CONTACT ANGLE: AS PER STANDARD;CAGE MATERIAL: AS PER STANDARD	0 6207C3
BEARING SPHRICAL ROLLER;23132CCK/W33;SKF	BEARING:SPHERICAL ; TYPE/MODEL DESIGNATION: 23132 CCK/W33BEARING BORE DIAMETER: 160 MMBEARING OUTSIDE DIAMETER:270 MMO OUTER RING WIDTH: 86 MMODEL: DOUBLE ROW SPHERICAL ROLLER BEARINGUSAGE LOCATION: USED FOR TENSIONER DEVICE ASSBLY SHIP LOADERADDITIONAL D	23132CCK/W33
SEAL;OIL;450X400X25;TYPE:MGT;FR31520 1	SEAL:OIL; OUTSIDE DIAMETER:450 MM ;INSIDE DIAMETER:400 MM ;WIDTH: 25 MM ;OPERATING TEMPERATURE RATING:125-180'C ;TYPE:MGT(SPLIT);STANDARD : JIS ; APPLICATION ROTARY KLIN	0
SEAL;OIL SEAL;CR 110X140X12 HMS5 RG	SEAL:NONMETALLIC SPECIAL SHAPED SECTION;OIL SEAL;INSIDE DIAMETER:110MM;OUTSIDE DIAMETER:140MM;STOCK THICKNESS:12MM;COLOR:BLACK;MATERIAL: NBR;TEMPERATURE RATING:100DEG C	CR 110X140X12 HM
SEAL OIL;CR130 X 160 X 15 HMSA 10 RG;SKF	SEAL: OIL; MANUFACTURER PART NUMBER :CR 130 X 160 X 15 HMSA 10 RG; INNER DIAMETER: 130MM; OUTER DIAMETER: 160 MM; THICKNESS: 15MM; TYPE: DOUBLE LIP; USAGE LOCATION : USED IN FLUID COUPLING YOXSSEZ 500;	CR 130 X160 X 15HM
SEAL OIL;CR140 X 170 X 15 HMSA 10 RG;SKF	SEAL: OIL; MANUFACTURER PART NUMBER :CR 140 X 170 X 15 HMSA 10 RG; INNER DIAMETER: 140MM; OUTER DIAMETER: 170 MM; THICKNESS: 15MM; TYPE: DOUBLE LIP; USAGE LOCATION : USED IN FLUID COUPLING YOXSSEZ 500;	CR 140 X 170 X 15HM
GREASE GUN;MANUAL;SKF	COUPLING:GREASE GUN; MODEL DESIGNATION: TLGH 1MAXIMUM PRESSURE: 40 MpaVOLUME/STROKE: APPROX. 1.5 CUBIC CENTIMETRE LENGTH : 3 80 MMDRIVE: MANUAL DISCHARGE PIPE LENGTH: 175 MM : 1077600 H;RESERVOIR : LOOSE GREASE (500 CM3) OR GREASE CATRIDGES.MAKE: S KFMA	1077600

SEAL OIL;55X90X10; DOUBLE LIP; VITON	SEAL:OIL; INSIDE DIAMETER: 55; OUTSIDE DIAMETER: 90SPECIFICATION/STANDARD DATA: 80X125X10; DOUBLE LIP; VITON	0
OIL SEAL *80*60*8 SKF	RETAINER:OIL SEAL; MATERIAL: NBRSTYLE DESIGNATOR:HSMA 10 SPECIFICATION/STANDARD DATA: SIZE 80*60*8 HSMA 10ADDITIONAL DATA: OIL S EAL 80*60*8;MAKE SKF;HSMA 10;DOUBLE LIP	806008
SEAL RETAINER FLRLSTMR 130MM 160MM	SEAL RETAINER; SEALING MATERIAL: FLUOROELASTOMER; HEIGHT: 12MM; INNER DIAMETER: 130MM; OUTER DIAMETER: 160MM; PROFILE: CLOSED W/O COVER; LIP TYPE: SINGLE LIP; TRACTION SPRING: W/TRACTION SPRING - 130X160X12 CRW1 V SKF	0
BEARING;BALL;DEEP GROOVE;6209 2RS	BEARING:BALL;DEEP GROOVE; STYLE DESIGNATOR: 6209 2RS;BORE SHAPE: CYLINDRICAL;BORE DIAMETER: 45 MM;OVERALL OUTSIDE DIAMETER: 85 MM OVERALL WIDTH: 19 MM;ROW QUANTITY: 1;CONTACT ANGLE: AS PER STANDARD;CAGE MATERIAL: AS PER STANDARD	62092RS
BEARING HOUSING; SNL 511-609;SKF	HOUSING:BEARING UNIT; SHELL TYPE:SNL 511-609;MATERIAL:G.C.I.;FORM CONSTRUCTION:SEAL MATERIAL:V.SEAL;SEA LING:RUBBER;MAKE:SKF	SNL511
BEARING ;6215 2RS	BEARING:BALL;BORE SHAPE: CYLINDERICALBORE DIAMETER: 75 MMOVERALL OUTSIDE DIAMETER: 130 MMOVERALL WIDTH: 25 MM: ACCESSORIES: B EARING SIZE 6215 -2RS;MAKE: SKF	6215
BEARING UNIT; SQUARE FLANGED;FYJ60TF	BEARING UNIT; BOX TYPE: SQUARE FLANGED; MATERIAL: CAST IRON; SHAFT DIAMETER: 60MM; BASE LENGTH: 68,7MM; FLANGE DIAMETER: 175MM; FIXATION BORE DIAMETER: 19MM; FIXATION BORE DISTANCE: 143MM; SEALING TYPE: DOUBLE RETAINER; MOUNTED BEARING: YAR 212-2F; LUBRI	0
CAPACITOR,MODLE:CBB24S,25µF,1000W	CAPACITOR,PHILIPS LUMINAIRE ONLY ,MODLE:CBB24S,CAPACITOR FOR HID, 25mF +-5PCT B,250VAC. 50/60HZ -40/105C 470K#/1W,COMPANY:PHILIPS LI GHTING LUMINAIRE(SHANGHAI)CO.LTD,MADE IN CHINA. (UNLOADER 1000W)	CBB24S
BALL BEARING 626 2Z SKF	BALL BEARING; TYPE: DEEP GROOVE; INNER DIAMETER: 6MM; OUTER DIAMETER: 19MM; WIDTH: 6MM; ROW QUANTITY: 1 ROW; MATERIAL: STEEL; CLEARANCE CLASS: NORMAL; CAGE MATERIAL: STEEL; ACTUATION LOAD: RADIAL; HOLE FORMAT: CYLINDRICAL; PROTECTION: DOUBLE PROTECTION -	0
BALL BEARING 6082Z SKF	BALL BEARING; TYPE: DEEP GROOVE; INNER	0

	DIAMETER: 8MM; OUTER DIAMETER: 22MM; WIDTH: 7MM; ROW QUANTITY: 1 ROW; MATERIAL: STEEL; CLEARANCE CLASS: NORMAL; CAGE MATERIAL: STEEL; ACTUATION LOAD: RADIAL; HOLE FORMAT: CYLINDRICAL; PROTECTION: DOUBLE SEALING - 60	
BALL BEARING 6005 SKF	BALL BEARING; TYPE: RIGID; INNER DIAMETER: 25MM; OUTER DIAMETER: 47MM; WIDTH: 12MM; ROW QUANTITY: 1 ROW; MATERIAL: STEEL; CLEARANCE CLASS: NORMAL; CAGE MATERIAL: STEEL; ACTUATION LOAD: RADIAL; HOLE FORMAT: CYLINDRICAL; PROTECTION: W/O PROTECTION - 950008	0
BALL BEARING 6009 2Z SKF	BALL BEARING; TYPE: DEEP GROOVE; INNER DIAMETER: 45MM; OUTER DIAMETER: 75MM; WIDTH: 16MM; ROW QUANTITY: 1; MATERIAL: STEEL; CLEARANCE CLASS: NORMAL; CAGE MATERIAL: STEEL; ACTUATION LOAD: RADIAL; HOLE FORMAT: CYLINDRICAL; PROTECTION: DOUBLE PROTECTION - 6	0
BALL BEARING 6008 2Z SKF	BALL BEARING; TYPE: RIGID; INNER DIAMETER: 40MM; OUTER DIAMETER: 68MM; WIDTH: 15MM; ROW QUANTITY: 1 ROW; MATERIAL: STEEL; CLEARANCE CLASS: NORMAL; CAGE MATERIAL: STEEL; ACTUATION LOAD: RADIAL; HOLE FORMAT: CYLINDRICAL; PROTECTION: DOUBLE PROTECTION - 600	0
BALL BEARING UC213D1 NTN	BALL BEARING; TYPE: BOLT FAST FIXATION; INNER DIAMETER: 65MM; OUTER DIAMETER: 120MM; WIDTH: 65,1MM; ROW QUANTITY: 1 ROW; MATERIAL: STEEL; CLEARANCE CLASS: NORMAL; CAGE MATERIAL: STEEL; ACTUATION LOAD: RADIAL; HOLE FORMAT: CYLINDRICAL; LUBRICATION: W/LUBR	0
BALL BEARING 40MM 60MM 13MM 51108 SKF	BALL BEARING; TYPE: BASIC STRUT; INNER DIAMETER: 40MM; OUTER DIAMETER: 60MM; WIDTH: 13MM; ROW QUANTITY: 1 ROW; MATERIAL: STEEL; CLEARANCE CLASS: NORMAL; CAGE MATERIAL: STEEL; ACTUATION LOAD: AXIAL; HOLE FORMAT: CYLINDRICAL; PROTECTION: W/O PROTECTION - 6	0
CYLNDRCAL RLLR BRNG F-554185.01.NUP INA	CYLINDRICAL ROLLER BEARING; INNER DIAMETER: 17MM; OUTER DIAMETER: 37MM; WIDTH: 14MM; MATERIAL: ALLOY STEEL; ROW QUANTITY: 1 ROW; ACTUATION LOAD: RADIAL; BORE SHAPE: CYLINDRICAL; CLEARANCE CLASS: NORMAL; CAGE MATERIAL: POLYAMIDE - F-554185.01.NUP INA	0